

SPECIFICATION ABOUT FORNA CORK FLOORING

	Cork floating flooring	Glue-down cork tile
Description	Cork floating floor with UNILIN click system	cork glue-down tile
Dimension	36" x 12" approx. (915mm x 305mm)	24" x 12" approx. (600mm x 300mm) 12" x 12" (305mm x 305mm)
Thickness	Thickness: 7/16" approx. (11mm)	approx. 3/16" (4mm) or (4.8mm)
Composition	Top cork layer: 3mm (nominally 1/8") Middle HDF: 7mm Bottom cork underlay for sound isolation: 1mm	Natural cork with polyurethane binder
Density Cork	Wear layer 450-500 or 500-550kg/m ³ (28-30lb/fts or 30-34lb/ft ³)	Wear layer 450-500 or 500-550kg/m ³ (28-30lb/fts or 30-34lb/ft ³)
Surface Finishing	Prefinished with 3 coats of water-based PU varnish	Prefinished with 3 coats of durable PU varnish
Sound absorption	approx. 14dB	approx. 14dB
Thermal resistance	approx. 0.129m ² K/W	approx. 0.129m ² K/W
Light fastness	Pale in sunlight	Pale in sunlight
Wear resistance	with the Taber Abrasion method – Wheels CS17, load 1000g	with the Taber Abrasion method – Wheels CS17, load 1000g
Packing	7 planks per pack or 1.9535 M ² 48 packs per pallet	(600mm x 300mm x 4mm) 11 pcs per pack or 1.98M ² 4 packs per carton 54 cartons per pallet

Storage

Planks must be stored horizontally